



HY-FLEX
CORP

INDUSTRY PROVEN SINCE 1970

**PROVEN
RELIABILITY**

**PORTABILITY & PRODUCTION
WITHOUT COMPROMISE**

HF-15 SPRAY BUDDY



**FIREPROOFING - STUCCO - EIFS - PLASTER - GROUT - CEMENT COATINGS
SYNTHETIC FINISHES - SPLATTER - DRYWALL**

TOLL FREE 866.849.6246

www.HYFLEXCORP.com

SPECIFICATIONS & CAPACITIES

Power	1 HP Electric
Power Requirement	110 Volt 15A
Pump Type	Optimized 2L3 Stator
Hopper Capacity	15 Gallon
Hopper Height	32"/81cm
Volume Control	Variable 0-2 gpm
Pressure Outout	200 PSI
Directional Control	Forward/Reverse
Controls	Manual/Remote
Machine Width	26"/66cm
Machine Length	54"/137cm
Machine Height	41"/104cm
Machine Weight	190 lbs/86kg
Wheels	12" OD Semi-Solid
Max Aggregate Size	.125"/3 mm
Max Pumping Distance	150' (Note: It can be greater or less)



HF-15 SPRAY BUDDY



HZ-30G

Power	13 HP Honda Gas Engine	Controls	Manual/Remote
Fuel Tank	1.7 Gal / 6.9 qts	Machine Width	33"/84cm (48"/122cm w/Tow Package)
Pump Output	0-10 gpm	Machine Length	84"/213cm
Pump Size	Optimized 2L6	Machine Height	42"/107cm
Air Output	12 cfm @ 90 psi	Machine Weight	675 lbs/ 306 kg
Hopper Capacity	60 Gal	Wheels - Rear	20" OD Pneumatic
Hopper Height	30 in / 76 cm	Wheels - Front	10" OD Pneumatic Casters
Volume Control	Variable 0-10 gpm	Max Aggregate Size	.125 in / 3 mm
Pressure Output	500 PSI Maximum	Max Pumping Distance	200' (Note: It can be greater or less)
Directional Control	Forward and Reverse	Optional Equipment	Tow Package



CM71

Power	3 HP	Machine Width	28"/71cm - 30"/76cm (with Platform)
Power Requirement	230 V Single Phase 20A	Machine Length	92.5"/235 cm (with 40" mix tube)
Mixer Output	70 Bags Per Hour	Machine Height	70.5"/179 cm
Hopper Capacity	3 Bags	Machine Weight	693 lbs/314 kg
Charge Height	54" / 137 cm	Wheels	8" Rigid and Swivel Casters
Volume Control	Single Speed	Optional Equipment	Water System
Max Aggregate Size	Fireproofing		Work Platform

HZ-30E



Power	5 HP Variable Speed	Controls	Manual/Remote
Power Requirement	208/240 V 30A	Machine Width	33" / 839 cm
	1 or 3 Phase	Machine Length	72" / 1829 cm
Air Output (optional)	12 cfm	Machine Height	43" / 1092 cm
Pump Size	Optimized 2L6	Machine Weight	585 lbs / 266 kg
Hopper Capacity	60 Gal	Wheels - Rear	15" / 38cm OD Pneumatic
Hopper Height	32" / 81 cm	Wheels - Front	10" / 25cm OD Pneumatic Casters
Volume Control	Variable 0-10 gpm	Max Aggregate Size	.125" / 3 mm
Pressure Outout	500 PSI Maximum	Max Pumping Distance	200' (Note: It can be greater or less)
Directional Control	Forward and Reverse	Optional Equipment	Air Compressor

321E



Power	15 HP Electric	Controls	Manual/Remote
Power Requirement	208/230 volt 50A 3 PH	Directional Control	Forward and Reverse
Pump Type	3" Dual Piston	Machine Width	28" / 71 cm
Air Output	12 cfm	Machine Length	62" / 157 cm
Pump Size	2" Ball Valve	Machine Height	34" / 86 cm
Pump Output	70 Bags Per Hour	Machine Weight	1350 lbs / 615 kg
Hopper Height	23" / 58 cm	Wheels	8" Rigid and Swivel Casters
Volume Control	Variable Hydraulic	Max Aggregate Size	.187 in / 5 mm
Pressure Outout	1000 psi / adjustable	Max Pumping Distance	550' maximum