

30G SPECIFICATIONS

POWER	Kohler Command Pro 14HP estimated (429cc)
FUEL TANK	Kohler 1.85 Gallon Gas Tank
SPEED CONTROL	Dial-a-Speed hydraulic speed control
CONTROLS	Mechanical & Electric hydraulic controls
PUMP OUTPUT	High Output model 11 gpm or 30 bags ¹ per hour High Torque model 8.5 gpm or 23 bags ¹ per hour
PUMP SIZE	Optimized 2L6 rotor & stator
PUMP HOPPER CAPACITY	60 gal/3 bags
PUMP CHARGE HEIGHT	32 in
PRESSURE OUTPUT	350 psi max recommended working pressure
DIRECTIONAL CONTROL	Forward and Reverse
REMOTE CONTROL	2 wire 125 ft On/Off remote standard (can be extended up to 500 ft total)
OVERALL DIMENSIONS	Wide Axle 48 W x 84 L x 42 H (in) Narrow Axle 35 W x 84 L x 42 H (in), (width 33 in without grate)
WEIGHT	Wide Axle 585 lbs, Narrow Axle 530 lbs
WHEELS -TOWABLE	Rear 20.5 X 4.80 X 12, Front 10 in swivel caster
WHEELS -NARROW	Rear 15 X 4.80 X 8, Front 10 in swivel caster
DRIVE	Hydraulic variable speed
PUMP OUTLET	2 in Camlock standard
MAX AGGREGATE SIZE***	1/8 in
RECOMMENDED PUMPING DISTANCE****	High Output* 150 ft High Torque** 200 ft
AIR OUTPUT	12 cfm @ 40 psi (90 psi max) onboard Chinook compressor

AVAILABLE OPTIONS
Truck Mount(TM), Gas Engine(G), Diesel Engine (D)
Wide axle -Towable
Narrow axle - Non-Towable
High Output* or High Torque**

¹ 1 bag = 3.0 cu ft yield
 * High output model recommended for use with products that pump more easily and a higher output is desired. Low-density fireproofing and self-leveling underlayments would be good choices.
 ** High torque model recommended for use with hard-to-pump products or extreme pumping distances or heights. Mortars and stuccos would fit this category.
 *** This is largest aggregate size recommended for pump. Mix design will determine how well product will pump.
 **** Pumping distance and output may be increased or decreased significantly depending on mix design, but we believe these to be very achievable in most instances.

Copyright 2018 Hy-Flex Corporation. All information contained within this document is based on the latest information available at the time of publication. Hy-Flex reserves the right to make changes at any time without notice.



APPLICATIONS

- Low/Medium/High-Density Fireproofing
- Waterproofing
- Plaster/Stucco Spraying
- Injection Work
- Manhole Restoration
- Concrete Repair Mortar
- Cellular Concrete
- Bridge Repair
- Self-Leveling Floor Underlayment
- Slab Jacking
- Cementitious Coatings Under 1/8 inch Aggregate

For parts, accessories or additional information, visit HyFlexcorp.com.



If you don't believe the hype about the 30G, try it out for yourself! This unit is available to rent from Hy-Flex. We offer monthly rates. Call 866-849-6246 for rates, recommendations and availability.



PRODUCT OVERVIEW

Speeding Up The Industry
One Pump At A Time

30G™

Rugged. Efficient.

BENEFITS

Look What Our Customers Say ...

MADE IN AMERICA

All metal fabrication and engineering is done in our Indiana facility

HEAVY DUTY

Made from durable materials/Built tough for years of reliable field use

LONG LIFE SPAN

Double-life stator tube outlasts the competition

PORTABLE

Small, lightweight, powerful/Easy to transport and use anywhere

HIGHLY DEPENDABLE

Most reliable rotor/stator drive available allows for more time on the job

EASY TO CLEAN

Removable bottom allows for cleanout in seconds; a simple hose does the rest



- Low maintenance seal design — long lasting and cost effective
- Daily maintenance limited to a single grease fitting
- Easy-access engine and hydraulics for quick maintenance
- Easy to understand and learn controls
- Very portable – Narrow axle and wide axle models easily fit into a long bed pickup truck/The wide axle model can be towed for quick trips across town
- Variable speed pump and mixer speed
- Can easily be towed with an ATV or UTV for remote locations
- Large pneumatic wheels and casters – improved mobility on the jobsite
- Electric start gets the machine up and running in no time
- All switches and relays sealed in watertight control box for reliability
- Wired remote for control at the gun
- Large inventory of parts! Orders placed by noon will be shipped out the same day

“We bought our first pump from Hy-Flex about 20 years ago. We have three pumps now, including the 30G. When we order parts, we receive them fast so it doesn’t impact our project schedule. Hy-Flex worked closely with us to make sure the pump we purchased would meet our production goals. They are always accessible and helpful.”



Ed St. Clair
Project Manager
Saint Plastering Systems, Inc.

“We’ve had great success using the HZ-30G for stucco applications on two recent projects. We successfully pumped 100 feet vertical and up to 250 feet overall. We’re especially impressed with the ease of use and the safety benefits compared to the much larger diesel engine pumps. The technical support was great and service has been easy. We look forward to using the HZ-30G even more and continuing our partnership with Hy-Flex for years to come.”



Jim Montgomery
V.P. Operations
Spectro Construction, Inc.

Portable & Powerful. Period.



Easily pumps traditional stucco



Easy-to-access engine and compressor



Removable hopper bottom offers easy cleanout and maintenance



Simple, easy-to-use controls