



BENEFITS

- Low maintenance seal design is very long lasting and cost effective.
- Single grease zerk is the only daily maintenance point.
- Easy-access controls offer standard toggle switches for easy field repair, unlike competitors' expensive membrane and touch panels.
- Operates on a 10k watt generator.
- Only four field-replaceable wear components to keep the unit running.
- Easy to understand and learn controls.
- Operates on 30A circuit – less breaker trips and onsite power issues than competitors.
- Totally sealed control box keeps electronics safe from water and dust.
- Very portable – easily fits into a short bed pickup truck.
- Large pneumatic wheels and casters –improved mobility on the jobsite.
- Large inventory of parts! Orders placed by noon will be shipped out the same day.

APPLICATIONS

- 3D Printing
- Acoustical Coatings
- Artificial Rock Structures
- Bridge Repair / Infrastructure Repair
- Cellular Concrete
- Cementitious Coatings Under 1/8 inch Aggregate
- Concrete Repair Mortar
- EIFS
- Fireproofing - Low/ Medium/High Density
- Grout Block Filling
- Injection Work
- Manhole Repair
- Plaster / Exterior Plaster
- Pool Coatings
- Stucco
- Self-Leveling Floor Underlayment
- Slab Jacking
- Texture Painting



POWER	5 hp electric inverter drive
SPEED CONTROL	Dial-a-Speed electronic speed control
PUMP OUTPUT	9 gpm or 23 bags per hour
PUMP SIZE	Optimized 2L6 rotor & stator
PUMP HOPPER CAPACITY	60 gal/3 bags
HOPPER HEIGHT	32"
PRESSURE OUTPUT	350 psi max recommended working pressure
DIRECTIONAL CONTROL	Forward and reverse
REMOTE CONTROL	2 wire 125' On/Off remote standard (can be extended up to 500' total)
WIDTH	35 in with grate/33 in without grate
HEIGHT	41"
LENGTH	75"
WEIGHT	545 lbs, bare machine
POWER REQUIREMENT	50/60 HZ 208/240 V 30 A single phase or 20 A three phase
PLUG CONFIGURATION	30A 250VAC 1Ph NEMA L6-30P
OPTIONAL HIGH VOLTAGE	10A 50/60 HZ 380/440 V three phase
WHEELS	15" pneumatic rear, 10" swivel caster front
DRIVE	Maintenance-free direct drive
PUMP OUTLET	2" camlock standard
MAX AGGREGATE SIZE*	1/8"
MAX PUMPING DISTANCE*	300'

See website for diagrams and more information.

"We have been using HyFlex pumps for more than 15 years now. We love the simplicity of the machines, the reliability, the ease of repairing and replacing parts and how few of parts have needed to be replaced in the time that we have had our HyFlex pumps."

Jim Nicholson
 Owner
 Firedog Fireproofing 1, LLC

AVAILABLE OPTIONS

- 5.9 cfm Oilless Gast compressor
- 12 cfm 2 hp Englo
- Low-profile mortar mixer hopper

