



BENEFITS

- Low maintenance seal design — *long lasting and cost effective.*
- Daily maintenance limited to a single grease fitting.
- Easy-access engine and hydraulics for quick maintenance.
- Easy to understand and learn controls.
- Very portable – Narrow axle and wide axle models easily fit into a long bed pickup truck. The wide axle model can be towed for quick trips across town.
- Variable speed pump and mixer speed.
- Can easily be towed with an ATV or UTV for remote locations.
- Large pneumatic wheels and casters — *improved mobility on the jobsite.*
- Electric start gets the machine up and running in no time.
- All switches and relays sealed in watertight control box for reliability.
- Wired remote for control at the gun.
- Large inventory of parts! Orders placed by noon will be shipped out the same day.

APPLICATIONS

- 3D Printing
- Acoustical Coatings
- Artificial Rock Structures
- Bridge Repair / Infrastructure Repair
- Cellular Concrete
- Cementitious Coatings Under 1/8 inch Aggregate
- Concrete Repair Mortar
- EIFS
- Fireproofing - Low/ Medium/High Density
- Grout Block Filling
- Injection Work
- Manhole Repair
- Plaster / Exterior Plaster
- Pool Coatings
- Stucco
- Self-Leveling Floor Underlayment
- Slab Jacking
- Texture Painting



POWER	KOHLER® Command Pro 14HP estimated (429cc)
FUEL TANK	KOHLER 1.85 Gallon Gas Tank
SPEED CONTROL	Dial-a-Speed hydraulic speed control
CONTROLS	Mechanical and Electric hydraulic controls
PUMP OUTPUT	8.5 gpm or 23 bags per hour
PUMP SIZE	Optimized 2L6 rotor and stator
PUMP HOPPER CAPACITY	60 gal/3 bags
PUMP CHARGE HEIGHT	32"
PRESSURE OUTPUT	350 psi max recommended working pressure
DIRECTIONAL CONTROL	Forward and reverse
REMOTE CONTROL	2 wire 125' On/Off remote standard (can be extended up to 500 ft total)
OVERALL DIMENSIONS	Wide Axle 48" W x 84" L x 42" H, Narrow Axle 35" W x 84" L x 42" H, (width 33" without grate)
WEIGHT	Wide Axle 585 lbs, Narrow Axle 530 lbs
WHEELS - TOWABLE	Rear 20.5 X 4.80 X 12, Front 10" swivel caster
WHEELS - NARROW	Rear 15 X 4.80 X 8, Front 10" swivel caster
DRIVE	Hydraulic variable speed
PUMP OUTLET	2" camlock standard
MAX AGGREGATE SIZE*	1/8"
RECOMMENDED PUMPING DISTANCE*	200'
AIR OUTPUT	12 cfm @ 40 psi (90 psi max) onboard Chinook compressor

See website for diagrams and more information.

"I've used almost every pump on the market. HyFlex pumps are the best! Simple, powerful and reliable are the best words I can use to describe these great machines. I could never see Specialty Spray Systems going back to the other pump makers. Ever."

Scott Sellers
 President
 Specialty Spray Systems


AVAILABLE OPTIONS

Truck Mount (TM), Gas Engine (G)

Wide axle -Towable

Narrow axle - Non-Towable

RECOMMENDED FOR 30G



9 cu. ft. mixer

*Depending on material and application



Hose Package