SPRAY BUDDYTM RELIABLE. POWERFUL. AMERICAN-MADE.



BENEFITS

- No daily maintenance other than cleaning.
- Easy-access controls offer standard toggle switches for easy field repair.
- · Controls similar to those of the 30E machine make it easier to train staff on equipment.
- · Easy to understand and operate controls.
- Operates on a 5k watt generator.
- Only four field-replaceable wear components to keep the unit running.
- · Operates on 15A 110V GFCI circuit for easy connection without nuisance trips.
- · Totally sealed control box keeps electronics safe from water and dust.
- Very portable easily fits into a short bed pickup truck.
- Large semi-pneumatic wheels offer improved mobility on the job site.
- Easy to clean - flat sides for easy scrape down and near zero waste on cleanout.
- Field serviceable no special tools needed.



866-849-6246 hyflexcorp.com/spraybuddy

APPLICATIONS

- 3D Printing
- Artificial Rock Structures
- Bridge Repair / Infrastructure Repair
- Cellular Concrete
- Cementitious Coatings Under 1/8 inch Aggregate
- Concrete Repair Mortar
- EIFS
- Grout Block Filling



- Injection Work
- Manhole Repair
- Plaster / Exterior Plaster
- Pool Coatings
- Stucco
- Self-Leveling Floor Underlayment
- Slab Jacking
- Texture Painting

SPRAY BUDDY

	GENERAL SPECIFICATIONS	SPRAY BUDDY
POWER	1 hp electric inverter drive	
SPEED CONTROL	Dial-a-Speed electronic speed control	
PUMP OUTPUT		0-1.75 gpm
PUMP SIZE	Optimized 2L3 rotor & stator	
PUMP HOPPER CAPACITY	15 gal or 2/3 bags	
PUMP CHARGE HEIGHT	32"	
PRESSURE OUTPUT	250 psi max recommended working pressure	
DIRECTIONAL CONTROL	Forward and reverse	
REMOTE CONTROL	2-wire remote can be extended up to 500'	AFS Auto Reverse
OPT.		2 wire 60' (18 m) lg
WIDTH	26"	
HEIGHT	41"	
LENGTH	54"	
WEIGHT	285 lbs with air compressor; 190 lbs without air compressor	
POWER REQUIREMENT	60 HZ 110 V 15 A one phase	
PLUG CONFIGURATION	15A 125VAC 1Ph NEMA 5-15P	
WHEELS	12" dia semi solid	
DRIVE	Direct drive lube for life gearbox	
PUMP OUTLET	1" camlock standard	
MAX AGGREGATE SIZE*	1/8"	
MAX PUMPING DISTANCE*		150'

See website for diagrams and more information.

"The Spray Buddy has allowed us to be more efficient in tight spaces, more productive in limited logistics and more creative with patch jobs and repairs. This is an excellent tool for our industry. It's extremely easy to use, and I highly recommend it."

John Ford President Ford Drywall & Stucco, Inc.







Call 866-849-6246 for rates, recommendations and availability | hyflexcorp.com/spraybuddy

Copyright 2022 HyFlex® Corporation. All information contained within this document is based on the information available at the time of publication. HyFlex reserves the right to make changes at any time without notice. Spray Buddy is a trademark of HyFlex Corporation.