## WATERMAX



## BENEFITS

- High level of accuracy.
- Batch consistency.
- More consistent yield from product.
- Saves money makes a bag of material go farther.
- More accurate than timers.

APPLICATIONS

- Improves product performance for bagged products.
- High level of accuracy.
- Batch consistency.
- More consistent yield from product.
- Saves money makes a bag of material go farther.
- More accurate than timers.
- Reduced user error and variability.
- Easy to operate controls.
- Steel frame and casters for durability and portability.
- Fork pockets for secure transport.



866-849-6246 hyflexcorp.com/watermax



## HYFLEXCORP.COM

## WATERMAX

POWER	110 V 60 hz, Amps depend on sump pump used, but 10 A total with typical ¾ hp pump
PUMP OUTPUT	Approx 33 gallons in 75 seconds with ¾ hp pump
PUMP SIZE	3⁄4 hp sump pump
TANK SIZE	Graduated 50 gallon
REMOTE CONTROL	50' On-Off
WIDTH	27"
LENGTH	38"
HEIGHT	61"
POWER REQUIREMENT	110V 15A circuit
PLUG CONFIGURATION	15A 125VAC 1Ph NEMA 5-15P
MEASUREMENT METHOD	Digital flow meter with high accuracy
WHEELS	10" Solid Casters
PUMP OUTLET	1" NPT outlet
MAX PUMPING DISTANCE	25' max recommended, longer hose increases time to dispense. 1" Minimum hose size

See website for diagrams and more information.

"HyFlex has been our equipment partner for many years. The quality of pumps is second to none, and their technical support is outstanding. We look forward to using HyFlex equipment for years to come."

**Robert F. Taglienti** Co-Owner East Coast Fireproofing Co.





Call 866-849-6246 for rates, recommendations and availability | hyflexcorp.com/watermax

Copyright 2022 HyFlex<sup>®</sup> Corporation. All information contained within this document is based on the information available at the time of publication. HyFlex reserves the right to make changes at any time without notice. WaterMax is a trademark of HyFlex Corporation.