

## BENEFITS


- Pumps materials more than 1000 feet horizontally and 30 stories vertically.
- Towable - has torsion axles for smooth towing.
- Lightweight and easily towed with 1/2 ton pickup truck.
- Hydraulic-powered 12 cu ft mixer with forward and reverse controls.
- Hydraulic dumping mixer allows the operator to quickly and efficiently dump loads of material all day long without tiring or getting injured.
- Twin dump cylinders to keep the tub balanced and ensure a long life.
- Unique dust cover that's easily lifted for occasional spray off of buildup and stays safely in place for dumping.
- Water bar available for dispensing water into the tub while helping suppress dust.
- Hydraulic pump includes two 20" long x 3" material cylinders for smooth delivery of the material.
- Fully variable hydraulic speed control allows full pumping speed range.

## OPTIONAL TELEMATICS PACKAGE

Full graphics control, output of warnings, maintenance, and alarms. Remote diagnostics services for troubleshooting. Front office dashboard for monitoring of current state, performance statistics, and location monitoring.

## MAINTENANCE

Maintenance has been made easier with the new valve body and manifold designs.



## GENERAL SPECIFICATIONS

<b>POWER</b>	Yanmar Tier 4 Final 3 cylinder direct injection diesel engine, 24.7 hp @ 2200 rpm as rated by the manufacturer
<b>PUMP CYLINDERS</b>	Fully hydraulic 3" dual piston pump
<b>PUMP HOPPER CAPACITY</b>	22 gallon/minute or 50 bags/hour fireproofing output
<b>MIXER TUB HEIGHT</b>	50"
<b>MIXER CAPACITY</b>	12 cu ft
<b>MIXER HOOD</b>	Dust suppression hood standard; Dust collecting hood optional
<b>MIXER FEATURES</b>	4 blades/rubber wipers, forward/reverse directions, cleanout on side of tub
<b>PRESSURE OUTPUT</b>	1,500 psi recommended max working/adjustable pressure control
<b>DRY VEHICLE WEIGHT</b>	3600 lbs
<b>DRIVE</b>	Dual cylinder hydraulic dump
<b>PUMP OUTLET</b>	2" HD coupling pump outlet standard
<b>AIR COMPRESSOR</b>	Approximately 14 cfm @ 40 psi
<b>TRAILER FEATURES</b>	17 ft long and 84 in wide, Torsion axle suspension, 5000 lb axle 8 lug hub, 2-5/16" ball coupler standard, 2" ball or pintle available on request

## APPLICATIONS

- Low/Medium/High-Density Fireproofing
- Plaster/Stucco Spraying
- Infrastructure Repair