



BENEFITS

- Low maintenance seal design — *long lasting and cost effective.*
- Easy-access engine and hydraulics for quick daily maintenance.
- Manual and electric controls give you variability at your command.
- Electric start.
- Backward (reverse) dumping mixer allows cleanup while pumping.
- Work platform keeps your feet dry and makes it easy to load the mixer.
- Variable pump and mixer speed
- Can easily be towed with an ATV or UTV to remote locations — *doesn't require a heavy-duty truck to transport.*
- 2L6 rotor & stator give exceptional performance with difficult materials.
- All switches and relays sealed in a watertight control box for reliability.
- Large inventory of parts! Orders placed by noon will be shipped out the same day.

APPLICATIONS

- Low/Medium/High-Density Fireproofing
- Waterproofing
- Plaster/Stucco Spraying
- Injection Work
- Manhole Restoration
- Concrete Repair Mortar
- Cellular Concrete
- Bridge Repair
- Self-Leveling Floor Underlayment
- Slab Jacking
- Cementitious Coatings Under 1/8" Aggregate



POWER	KOHLER® Command Pro 14HP estimated (429cc)
FUEL TANK	KOHLER 1.85 Gallon Gas Tank
SPEED CONTROL	Dial-a-Speed hydraulic speed control
CONTROLS	Mechanical and Electric hydraulic controls
PUMP OUTPUT	4.5 gpm or 12 bags per hour
PUMP SIZE	Optimized 2L6 rotor & stator
PUMP HOPPER CAPACITY	60 gal/3 bags
PUMP CHARGE HEIGHT	32"
MIXER CAPACITY	4.5 cu ft
MIXER CHARGE HEIGHT	40" from platform
MIXER FEATURES	4 blades/rubber wipers, forward/reverse directions, dump forward and backward for cleanout, variable speed preset 45 rpm
PLATFORM SPECIFICATIONS	600 lb capacity, foldable/removable, 36" W x 36" L x 19" H
PRESSURE OUTPUT	350 psi max recommended working pressure
DIRECTIONAL CONTROL	Forward and reverse
REMOTE CONTROL	2 wire 125' On/Off remote standard (can be extended up to 500' total)
OVERALL DIMENSIONS	GM 66" W x 140" L x 68" H
WEIGHT	GM 1380 lbs; Truck Mount (TM) 1250 lbs
WHEELS	Rear 175/80R13
DRIVE	Hydraulic variable speed
PUMP OUTLET	2" camlock standard
MAX AGGREGATE SIZE*	1/8"
RECOMMENDED PUMPING DISTANCE*	150'
AIR OUTPUT	12 cfm @ 40 psi (90 psi max) onboard Chinook compressor
STANDARD FEATURES	Electric start, rubber isolated engine mounts, reversible
TRAILER FEATURES	4 prong flat plug, submersible LED rear lights, 2" ball receiver, independent torsion axles, jack w/caster

See website for diagrams and more information.

"We sprayed approximately 30 truckloads of material with our 30GM. It was very useful to have such a productive machine in a tight area. Our customer was impressed with the way we could use the machine and not interfere with other crafts. Our 30GM still has all the original wear parts and it's still pumping great."

David Wilson
Construction Manager, Marquis Construction Services, Inc.

AVAILABLE OPTIONS

Truck Mount (TM), Gas Engine (G)

Adjustable Stator

